Product datasheet

Specifications



Symmetra PX Battery Frame for 400V PX 96/160kW & 208V PX 100kW with 9 Battery Modules & Startup

SYCFXR9-9

Overview

Lead Time	Usually Ships within 8 Weeks

Main

Battery Type	VRLA
Provided Equipment	Installation guide User manual

Batteries & Runtime

Number Of Battery Blocks Per String	4
Number Of Battery Free Slots	0
Number Of Battery Filled Slots	9
Device Mounting	19 inch battery tray
Additional Information	Request SYBT9-B4 for replacement battery

Physical

Colour	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Net Weight	1209 kg
Usb Compatible	No

Conformance

Standards	EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 UL 1778
Product Certifications	CE EUROBAT

Environmental

Ambient Air Temperature For Operation	0…40 °C
Operating Altitude	0...3333 ft
Relative Humidity	0…95 %
Ambient Air Temperature For Storage	-15…40 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Storage Altitude	0.00…15240.00 m
Storage Relative Humidity	0…95 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	121 cm
Package 1 Length	84.8 cm
Package 1 Weight	1343 kg

Contractual warranty

Warranty	1 year repair or replace

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Learn more about Green Premium >


Take-back


Transparency


RoHS/REACh

Resource performance

- Take-Back Program Available

Well-being performance

- Lead Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile