overview	
Delivery date	Usually available from stock
main information	
Main Input Voltage	230 V 400 V 3 phase
product type	Uninterruptible power supply (UPS)
Other Input Voltage	220V 240V 380V 415V
Main Output Voltage	230 V
Other Output Voltage	220V 240V
Rated power [W]	11200 W
Rated power[VA]	16000 VA
output connection type	8 IEC 60320 C13 10 IEC 60320 C19
Output connector type	Hardwire 3-wire (HN + E) 1
Number of rack units	19U
Battery Type	Lead-acid batteries
Included equipment	Software CD Documentation CD Installation Guide User Manual Web SNMP Management Card
Battery and run time	
Pre-installed battery	0
Empty battery slot	4
Other parameters	Can be set to 220, 230 or 240 output voltage
battery life	3…5 years
Automatic detection and scalable delay time	1
Universal	
Number of free power module slots	5
Number of populated power module slots	0
redundancy	Yes
Physical parameters	
color	Black silver medal
high	83.8 cm
width	47.2 cm
depth	68.8 cm
net weight	95.45 kg
Installation location	Front
Installation preferences	Lower
Installation type	Rack-mounted
Can be mounted on double posts	0
USB compatible	No
enter	
Network frequency	45...65 Hz auto-sensing
Enter the number of connectors	1 Hardwired 3-wire (1PH+N+G) 1 Hardwired 5-wired (3PH+N+G)
Input voltage limit	155...276 V 290...480 V 3:1
Input Power Factor at Full Load	0.98
output	
Maximum configurable power (watts)	11200 W
harmonic distortion	Less than 5% at full load
Output frequency (synchronized with main frequency)	47...63 Hz synchronized to main frequency 60 Hz +/- 0.1 % 60 Hz desynchronized to nominal value 50 Hz +/- 0.1 % 50 Hz desynchronized to nominal value
Crest coefficient	Up to 5 : 1
topology	Double conversion online
Waveform type	Sine wave
Bypass type	Internal bypass (automatic and manual)
power	90 % (full load)
Maximum output current	73 A
Maximum configurable power (volt-ampere)	16000 VA
environment	
operating temperature	0…40 °C
Relative humidity	5…95 %
Working altitude	0...10000 ft
Storage ambient temperature	-15…45 °C
Storage relative humidity	5…95 %
Storage height	0.00…4572.00 m
sound level	62 dBA
Dissipate heat when running online	3707 Btu/h
Communications and Management	
free slot	1
Pre-installed SmartSlot™ card	Network management card 2 with environmental monitoring - Schneider
Alarm function	Multifunctional LCD status management console.
Alarm	Audible and visible alarms : prioritized by severity
emergency shutdown	Yes
packaging unit	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	105.4 cm
Package 1 Width	99.7 cm
Package 1 Length	59.9 cm
Package 1 Weight	120.45 kg
Contract warranty	
Warranty	Repair or replace within 2 years

Show more specs ⌃