summary	
delivery date	Usually available from stock
main information	
product type	Replacement battery cartridge
Battery Type	Lead-acid batteries
equipment provided	All Connectors Needed Battery Recycling Guide Reusable Packaging Installation Guide
Battery and Runtime	
Number of battery blocks in each bar	2
empty battery slot	0
pre-installed battery	0
installation method	Independent battery stack
voltage	24V
RBC™ Quantity	1
Venturi Pipe	
physical parameters	
high	10.8 cm
width	13.2 cm
depth	15cm
product weight	5kg
installation type	Not rack-mountable
USB compatible	No
output	
Battery capacity	7.0 Ah
environment	
operating temperature	0…40°C
working altitude	0...10000ft
Relative humidity	0…95 %
storage environment temperature	-15…45°C
storage height	0.00…15240.00 m
storage relative humidity	0…95 %
packaging unit	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.800 cm
Package 1 Width	22.400 cm
Package 1 Length	16.800 cm
Package 1 Weight	5.910 kg
Unit Type of Package 2	S03
Number of Units in Package 2	2
Package 2 Height	30.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	11.820kg
Unit Type of Package 3	P12
Number of Units in Package 3	32
Package 3 Height	80.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	189.120 kg
contract warranty	
Warranty	2 Year Repair or Replacement Service

show more specifications ⌃