overview	
Exterior	APC's metered rack power distribution units (PDUs) feature active metering for energy optimization and circuit protection. User-defined alarm thresholds reduce risk with real-time local and remote alarms to warn of potential circuit overloads. Metered rack PDUs provide power usage data that allows data center managers to make informed decisions about load balancing and sizing IT environments, thereby reducing total cost of ownership. Metered rack PDUs include real power monitoring, temperature/humidity sensor ports, locking IEC receptacles, and very compact circuit breakers. Users can access and configure rack PDUs through a secure Web, SNMP or Telnet interface using APC's InfraStruXure InfraStruxure Central, Operations, Capacity and Energy Efficiency software Central management platforms appreciate these interfaces.
Delivery date	Usually available from stock
main information	
color	Black
product type	PDU
PDU type	Instrument testing
Cord length	1.8 m
Cable quantity	1
Equipment provided	Installation Guide Rack Mount Bracket Serial Configuration Cable Safety Guide
Additional information	
Input Voltage	400 V 3 phase
high	182.9 cm
width	5.6 cm
Output Voltage	240 V
depth	5.1 cm
net weight	10.1 kg
Installation location	Side
Installation preferences	No preference
Input Plug Type	IEC 60309 60 A 3P + N + E
Installation type	Rack-mounted
Rated current[In]	32 A
Input current limits	40 A
load capacity	23000 VA
Network frequency	50/60 Hz
Outlet type and quantity	30 IEC 60320 C13 12 IEC 60320 C19
environment	
certified product	cUL listed UL VCCI Class A
Standards compliant	EN 55022 Class A EN 55024 EN 61000-3-2 EN 61000-3-3 FCC 15 Part A Class ICES-003
operating temperature	-5…60 °C
Relative humidity	5…95 %
Working altitude	0...10000 ft
Storage ambient temperature	-25…65 °C
Storage relative humidity	5…95 %
Storage height	0.0000000000…15240.0000000000 m
packaging unit	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	214.9 cm
Package 1 Width	11.2 cm
Package 1 Length	22.1 cm
Package 1 Weight	14.05 kg
Contract warranty	
Warranty	Repair or replace within 2 years

Show less specs