Product datasheet

Specifications



RACK PDU, BASIC, 0U/1U, 120-240V/15A, 220-240V/10A, (8) C13

AP6015A

Overview

Lead time	Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Provided equipment	Installation guide Safety guide

Complementary

Input Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Height	24 cm
Width	4.4 cm
Output Voltage	100 V 120 V 200 V 208 V 230 V 240 V
Depth	9.3 cm
Net weight	0.91 kg
mounting location	Front Rear
Mounting preference	No preference
Input Plug Type	IEC 60320 C14
mounting mode	Not rack-mountable
Rack units	1U
Mounting position	Horizontal
[In] rated current	12 A
Permissible voltage	100…240 V
Max line current	15 A
Input current limits	15 A

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Load capacity	2300 VA
Network frequency	50/60 Hz
Outlet type and quantity	8 IEC 60320 C13

Environment

Product certifications	cUL listed CE EAC IRAM UL listed VDE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	28.6 cm
Package 1 Width	13 cm
Package 1 Length	21 cm
Package 1 Weight	1.37 kg
SCC14	10731304327797

Contractual warranty

Warranty	2 years repair or replace

Sustainability

Green Premium^{TM} label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Learn more about Green Premium >






Energy Efficient Take-back Transparency RoHS/REACh

Resource performance

- Energy Efficient Product
- Take-Back Program Available

Well-being performance

- Lead Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information