Product datasheet

Specifications



Rack PDU, Basic, 0U/1U, 220-240V, 63A, (3) C19

AP6038A

Overview

Lead time	Usually in Stock

Main

Colour	Black
Product or component type	PDU
PDU type	Basic
Cord length	3.7 m
Provided equipment	Installation guide Safety guide

Complementary

Input Voltage	230 V 240 V
Height	4.4 cm
Width	38.8 cm
Depth	12.6 cm
Net weight	5.4 kg
mounting location	Front
Mounting preference	No preference
Input Plug Type	IEC 60309 63 A 2P + PE
mounting mode	Not rack-mountable
Rack units	1U
Mounting position	Horizontal
Permissible voltage	200…240 V
Max line current	48 A
Input current limits	48 A
Load capacity	14500 VA
Network frequency	50/60 Hz
Outlet type and quantity	3 IEC 60320 C19

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	CE EAC IRAM VDE

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.5 cm
Package 1 Width	19.5 cm
Package 1 Length	50 cm
Package 1 Weight	8.3 kg

Contractual warranty

Warranty	2 years repair or replace

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO_2 products.

Learn more about Green Premium >


Energy Efficient


Take-back


Transparency


RoHS/REACh

Resource performance

- Energy Efficient Product
- Take-Back Program Available

Well-being performance

- Toxic Heavy Metal Free
- Mercury Free
- Rohs Exemption Information — Yes

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information