summary	
delivery date	Usually delivered within 2 weeks
main information	
Main Input Voltage	220 volts 230 volts
Main Output Voltage	220V 230V
Rated power [W]	600W
Rated power [VA]	1000VA
Battery Type	AGM
Attached equipment	Basic UPS Signaling RS-232 Cable User Manual
Battery and Runtime	
pre-installed battery	0
empty battery slot	0
Battery power in VAH	0 VAh runtime
Auto-detectable, scalable delay time	0
universal	
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
physical parameters	
high	18.2 cm
width	13cm
depth	32cm
product weight	7.8kg
Mounting preference	No preference
installation type	Not rack-mountable
Two post mountable	0
USB compatible	No
enter	
Network frequency	50/60Hz
output	
Maximum Configurable Power (Watts)	600W
Waveform type	Square wave
Maximum configurable power in VA	1000VA
conversion time	4 ms typical: 8 ms max
compliance	
Standards compliant	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
environment	
sound level	40 dBA
packaging unit	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	27.5cm
Package 1 Width	39cm
Package 1 Length	19.2 cm
Package 1 Weight	9.2kg
SCC14	00731304332688
contract warranty	
Warranty	Repair or replace within 2 years

show less specs