summary	
delivery date	Usually delivered within 2 weeks
main information	
Main Input Voltage	220 volts 230 volts
Main Output Voltage	220V
Rated power [W]	360W
Rated power [VA]	650VA
Battery Type	AGM
Attached equipment	Basic UPS Signaling RS-232 Cable Software CD
Battery and Runtime	
pre-installed battery	0
empty battery slot	0
Battery power in VAH	0 VAh runtime
Auto-detectable, scalable delay time	0
universal	
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
physical parameters	
high	14.2 cm
width	10.1 cm
depth	30cm
product weight	4.4kg
Mounting preference	No preference
installation type	Not rack-mountable
Two post mountable	0
USB compatible	No
enter	
Network frequency	50/60Hz
output	
Maximum Configurable Power (Watts)	360W
Output frequency (synchronized with main frequency)	50 Hz synchronized to main frequency
Waveform type	Square wave
Maximum configurable power in VA	650VA
conversion time	4 ms typical: 8 ms max
compliance	
Standards compliant	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
environment	
sound level	40 dBA
packaging unit	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22cm
Package 1 Width	34.4 cm
Package 1 Length	14cm
Package 1 Weight	5.4 kg
SCC14	10731304332692
contract warranty	
Warranty	Repair or replace within 2 years

show less specs