Product datasheet

Specifications



APC Netshelter Rack Automatic Transfer Switch, 2U, 32A, 230V, 2 IEC 309 IN, 16 C13, 2 C19 OUT, 50/60 Hz

AP4424A

Overview

Lead time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Main Output Voltage	230 V AC 1 phase
Input Connection Type	IEC 60320 IEC 60309 32 A 2P + E IEC 60320
Number of rack unit	2U
Cable length	2.44 m
Number of cables	2
Provided equipment	Mounting hardware Rack mounting brackets Serial configuration cable

Physical

Colour	Black
Height	8.8 cm
Width	43.2 cm
Depth	23.6 cm
Product weight	6.94 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted
Mounting position	Horizontal

Input

Network frequency	50/60 Hz
Permissible voltage	207…253 V
Load capacity	7400 VA

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Output

Max current draw	32 A
Number of power socket outlets	18
Protection type	Circuit breaker

Conformance

Product certifications	EN 55022 class A FCC part 15 class A
Standards	EN 55022 class A FCC part 15 class A

Environmental

Ambient air temperature for operation	-5…45 °C
Relative humidity	5…95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25…65 °C
Storage Relative Humidity	5…95 %

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21 cm
Package 1 Width	58.4 cm
Package 1 Length	35.6 cm
Package 1 Weight	9.43 kg
Unit Type of Package 2	PAM
Number of Units in Package 2	20
Package 2 Height	120 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	201.2 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace

Recommended replacement(s)