summary	
Delivery date	Usually delivered within 6 weeks
main information	
Main Input Voltage	220 volts
Other Input Voltage	230V 240V
Main Output Voltage	220 V 230 V 240 V
Other Output Voltage	230V 240V
Rated power [W]	6000W
Rated power [VA]	6000VA
Output connector type	Hardwire 3-wire (HN + E) 1
Battery Type	External battery system
Included equipment	Basic UPS signaling RS-232 line 1 DC cable software CD user manual USB cable
Battery and run time	
Other parameters	Can be set to 220, 230 or 240 output voltage
voltage	240V
Automatic detection and scalable delay time	0
Battery charging voltage (watts)	1170W rated
Universal	
Redundant	No
Physical parameters	
color	Black
high	33.6cm
width	19 cm
depth	37.4 cm
net weight	13kg
Mounting preference	No preference
Installation type	Not rack-mountable
Two post mountable	0
USB compatible	Yes
enter	
Input voltage limit	110...300 V half load 176...300 V full load
Number of input connectors	1 Hardwire 3-Wire (1PH+N+G)
Network frequency	40...70 Hz auto-sensing
output	
bypass type	Internal bypass (automatic and manual)
Crest coefficient	3:1
Maximum configurable power in VA	6000VA
Maximum configurable power (watts)	6000W
topology	Double conversion online
Waveform type	Sine wave
power	94% (full load)
Output frequency (synchronized with main frequency)	50/60 Hz +/- 3 Hz synchronized with main frequency
conformity	
certified product	CE
environment	
sound level	55 dBA
Working altitude	0...3000m
operating temperature	0…40°C
Storage ambient temperature	-15…60 °C
Storage height	0…15000m
IP protection level	IP20
Relative humidity	0…95 % non-condensing
Storage relative humidity	0…95 % non-condensing
Communications and Management	
alarm	Alarm when on battery: distinctive low battery alarm: overload continuous tone alarm
emergency shutdown	Yes
free slot	1
Alarm function	Multifunctional LCD status management console.
Surge protection and filtering	
Surge suppression energy	600 J
packaging unit	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	46 cm
Package 1 Width	49.1cm
Package 1 Length	29 cm
Package 1 Weight	16kg
SCC14	10731304343216
Contract warranty	
Warranty	Repair or replace within 2 years

Show less specs ^